

## Multimedia Converter, De-interlacer & Switcher



The EL-5300 will convert, de-interlace & Switch all your analogue and digital devices to HDMI. All standard definition inputs can be de-interlaced for compatibility with all HDMI displays and supports up to 16 bit Deep Colour together with High Definition audio.

### FEATURES

- v1.3 HDMI, HDCP 1.1 and DVI 1.0 compliant
- Multimedia Converter, De-Interlacer & Switcher
- Resolutions supported:
  - PC - VGA to SXGA @ 60Hz;
  - HDTV 480i to 1080p plus 1080p24fps
- Accepts a variety of analogue/digital video & audio inputs
- Format conversion from 480i/576i to 480p/576p (de-interlaced)
- RS-232 & IR remote Control
- HDMI I/O Supports 'Deep Colour' (10 & 12 bit)
- Supports 150ms audio delay - NOTE: This feature will not function when input is from HDMI source
- 3D noise reduction (DNR) & Comb Filtering
- Supports 3D signals

### SPECIFICATIONS

|               |  |
|---------------|--|
| Input:        | 3x HDMI (3x HDMI (bypass) - Uncompressed AV and Data), 2x RCA (2x Composite), 2x S-video plug (2x S-video), 8x RCA (4x Analogue Stereo (L/R)), 6x RCA (2x YCbCr Component / YPbPr Component), 1x 15pin Dsub (1x Analogue RGBHV), 1x Stereo mini-jack (1x Analogue (PC) Stereo(L/R)), 1x 9pin Dsub (1x RS-232 Data) |
| Output:       | 1x HDMI (1x HDMI Uncompressed AV and Data)   |
| Power:        | 5V/2.6A DC (US/EU standards, CE/FCC/UL certified)  |
| Dimensions:   | 280mm (W) x 150mm (D) x 48mm (H)   |
| Gross Weight: | 1340g  |
| Net. Weight:  | 940g   |
| Packaging:    | Retail Packaged  |

